



### Typical Inspection Data:

|                    |                         |
|--------------------|-------------------------|
| Density @ 20 °C    | 0.860 g/cm <sup>3</sup> |
| Viscosity @ 100 °C | 7.1 cSt                 |
| Viscosity @ 40 °C  | 46 cSt                  |
| Viscosity Index    | 110                     |
| Zinc               | 0.08%                   |
| Phosphorus         | 0.05%                   |
| Colour             | Straw                   |
| Pour Point         | -33 °C                  |

## LIC 15

### Hydraulic Oil

**Recommended by Comma for applications requiring:**

ISO VG 46

### Product Features:

- Suitable for hydraulic systems of excavators, construction equipment and fork lift trucks.
- Ideal for tipping gear, fluid couplings, some torque converters, tail and garage lifts.
- Also suitable for jacks.
- Enhanced low-temperature properties for all seasons use.

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

31-10-17