



Typical Inspection Data:

| | |
|-----------------------|-------------------------|
| Density @ 20°C | 0.850 g/cm ³ |
| Viscosity @ 100°C | 12.2 cSt |
| Viscosity @ 40°C | 70 cSt |
| Viscosity Index | 165 |
| Viscosity CCS @ -30°C | 6000 cP |
| T.B.N. | 7.8 mg KOH/g |
| Sulphated Ash Mass | 0.8% |
| Zinc | 0.10% |
| Calcium | 0.18% |
| Phosphorus | 0.08% |
| Colour | Brown |
| Flash Point | 230°C |
| Pour Point | -39°C |

Syner-Z 5W-30

Fully Synthetic

Official Approvals:

MB 229.31, MB 229.51, MB 229.52

Recommended by Comma for applications requiring:

BMW LL-04; dexos 2, VW 502 00, VW 505 00, VW 505 01; ACEA C2, C3; API SN CF

Product Features:

- Fully synthetic, high performance 5W-30 low SAPS oil for modern petrol and diesel vehicles including those fitted with exhaust after-treatment units that require an ACEA C3 grade.
- For modern BMW, MB and GM vehicles including those operating with long life service intervals.
- Do not mix this oil with other types of oil, as the requirement for exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 14-11-2018