



Typical Inspection Data:

Density @ 20 °C	0.865 g/cm ³
Viscosity @ 100 °C	14.4 cSt
Viscosity @ 40 °C	95 cSt
Viscosity Index	150
Viscosity CCS @ -25 °C	5400 cP
T.B.N.	10.3 mg KOH/g
Sulphated Ash Mass	1.5%
Zinc	0.12%
Calcium	0.36%
Phosphorus	0.12%
Colour	Dark Brown
Flash Point	230 °C
Pour Point	-33 °C

TransFlow AD 10W-40 Semi Synthetic

Recommended by Comma for applications requiring:

ACEA A3/B4 E7; API CI-4
MAN 3275; Cummins CES 20077/78; MTU Type 2; MACK EO-M+

Official Approvals:

TransFlow AD 10W-40 is officially approved by:
MB-Approval 228.3; Volvo VDS-3; Renault RLD-2; MACK EO-N

Product Features:

- Semi-synthetic, 10W-40 oil, suitable for high performance diesel engines including turbo charged and naturally aspirated.
- Ideal for mixed fleet-trucks.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

23-01-2017