

Technical Data Sheet



Typical Inspection Data: Density @ 20°C 0.844 g/cm³ Viscosity @ 100°C 8.5 cSt Viscosity @ 40°C 44 cSt Viscosity Index 174 Viscosity CCS @ -35°C 6000 cP T.B.N. 7.4 mg KOH/g Sulphated Ash Mass 0.7% Zinc 0.08% Calcium 0.13% **Phosphorus** 0.07% Colour Brown Flash Point 230°C **Pour Point** -39°C

Pro-NRG 0W-20

Fully Synthetic

Recommended by Comma for applications requiring:

GM dexos1 Gen3, GM dexos1 Gen2 (backward compatible); API SP; ILSAC GF-6A; Chrysler MS 6395; GM 6094M & GM 4718M

Product Features:

- Fully synthetic, high performance 0W-20 oil for modern petrol vehicles.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 30-06-2023